

P.O. Box 39353 • Lakewood, Washington 98496

O 253.830.3366 F 253.830.5863 E info@Castohn.com

Castohn.com

CASTOHN[®]
true to form

Specification Sheet (short form)

Product

Olympic Paver Collection

Color

Standard Color – Charcoal

Please note that special order color is available. Contact Castohn Representative for more information.

Finish

Sand exposed

Size	Actual	Weight
12 x 24 x 2-1/2"	11-7/8 x 23-7/8 x 2-1/2"	65 pounds
12 x 36 x 2-1/2"	11-7/8 x 35-7/8 x 2-1/2"	95 pounds
12 x 48 x 2-1/2"	11-7/8 x 47-7/8 x 2-1/2"	125 pounds
24 x 24 x 2-1/2"	23-7/8 x 23-7/8 x 2-1/2"	125 pounds
24 x 48 x 2-1/2"	23-7/8 x 47-7/8 x 2-1/2"	250 pounds
36 x 36 x 2-1/2"	35-7/8 x 35-7/8 x 2-1/2"	285 pounds

Physical Properties

Compressive strength	>6,000 psi
Flexural strength	>600 psi
Water absorption	<6%
Dimensional Tolerance length and width	±3/16"
Dimensional Thickness	±1/8"

Technical Data: American Society for Testing & Materials (ASTM)

ASTM C33 – Standard Specification for Concrete Aggregates

ASTM C39 – Concrete Compressive Strength

ASTM C150 – Standard Specification for Portland Cement

ASTM C642 – Water Absorption, Density, Voids in Hardened Concrete

ASTM C979 – Pigments for Integrally Colored Concrete

MANUFACTURER OF:

ROSETTA[®]
WALLS • STEPS • ACCENTS

ECOcrete[®]
Concrete Ecological Solutions

CASTOHN[®]
ARCHITECTURAL ACCESSORIES